

# WATER LOGIC WL2

## Water Dispenser

### General features

- ✓ 4 Litre cold water tank
- ✓ Variable water temperature settings 5 - 7°C
- ✓ LED UV fault indicator for easier servicing
- ✓ High performance filtration
- ✓ BioCote® protection
- ✓ Water dispensing area - 230mm (H)
- ✓ Compact design with aesthetically pleasing looks
- ✓ Low maintenance
- ✓ Mains fed - Easy connection to existing mains water supply
- ✓ Drip tray capacity 360ml

### Firewall technology

- ✓ Waterlogic's patented and exclusive Firewall technology utilises a highly effective UVC purification system that acts at the point of dispense.
- ✓ Firewall guarantees up to 99.9999% bacteria free water

### High performance filtration

- ✓ Waterlogic's carbon filters are certified to stringent standards, carrying the Water Quality Association's (WQA) Gold Seal of approval, meaning they offer the best possible filtration

### BioCote® protection

- ✓ The key plastic surfaces surrounding the dispensing area are infused with BioCote™, a silver ion additive that provides continuous antimicrobial protection against a broad spectrum of bacteria and mould



Excellent purifying performance, easy operation and stylish design

Purified water for the workplace



### Machine Specifications

Types available	Freestanding and countertop
Dispensing area height	230 mm
Standard filtration supplied	Carbon block with lead, cyst, and asbestos reduction
Storage capacity	Hot tank: 1.5 L Cold tank (Freestanding): 4 L Cold tank (Countertop): 2 L
Compressor	Compressor (R134a) 120V/60Hz

Water temperature settings	Cold: 3°/ 5°/ 7°C (default 5°C) Hot: 85-87°C (default 85°C)
Dimensions (HxWxD)	Freestanding: 102cm x 35cm x 36cm Countertop: 47cm x 35cm x 36cm
Weight	Countertop: 19kg Freestanding: 26.3kg
Colour options	 